

## 活塞式蓄能器/Piston accumulator

### ❖ 一、概述/General Description

HXQ系列活塞式蓄能器,由本公司自行研究设计制造,产品规格齐全,可根据用户不同要求设计制造。本产品有结构新颖,密封性能好,无泄漏,耐高压,使用寿命长等特点。

HXQ series piston type accumulator, designed by our factory, with complete product specifications. we can design according customer request. Piston accumulator advantage with good sealing, no leakage, high temperature resistance, long service life.

### ❖ 二、型号说明/Ordering Code



### ❖ 三、内部结构及外形尺寸 Structure and Dimension



型号/Model	公称压力 Nominal P MPa	公称容积 Nominal V L	基本尺寸Dimensions (mm)			重量/Weight (Kg)	
			$\Phi D$	M	$\Phi D_1$		
HXQ-※-0.22/※-※-63		0.22	63	M22X1.5	35	225	9.5
HXQ-※-0.49/※-※-63		0.49				310	10.9
HXQ-※-1/※-※-63		1				470	13.8
HXQ-※-2/※-※-63		2				800	19.8
HXQ-※-0.49/※-※-65		0.49	65	M27X1.5	35	280	-
HXQ-※-1/※-※-65		1				430	-
HXQ-※-1/※-※-80	10-99	1				380	19.4
HXQ-※-2/※-※-80		2				580	24.3
HXQ-※-2.5/※-※-100		2.5	100	M42X2	50	530	36.5
HXQ-※-3.5/※-※-100		3.5				660	41.4
HXQ-※-5/※-※-100		5				850	48.6
HXQ-※-6/※-※-100		6				975	53.4
HXQ-※-7.5/※-※-100		7.5				1170	60.7
HXQ-※-2/※-※-125		2	125	M42X2	50	350	35
HXQ-※-4/※-※-125	10-42	4				485	-
HXQ-※-5/※-※-125		5				590	50
HXQ-※-10/※-※-180		10	180	M60X2	70	655	86.8
HXQ-※-16/※-※-180		16				890	140.4
HXQ-※-20/※-※-180		20				1050	155.8
HXQ-※-25/※-※-180		25				1250	175
HXQ-※-32/※-※-180	10-42	32				1520	200.9
HXQ-※-35/※-※-180		35				1645	213.9
HXQ-※-39/※-※-180		39				1800	227.7
HXQ-※-45/※-※-180		45				2030	249.8
HXQ-※-50/※-※-180		50				2235	270
HXQ-※-8/※-※-195		8	195	M60X2	70	550	-
HXQ-※-10/※-※-195		10				615	-
HXQ-※-20/※-※-195	20	20				950	-
HXQ-※-32/※-※-195		32				1350	-
HXQ-※-40/※-※-195		40				1620	-
HXQ-※-50/※-※-195		50				1955	-
HXQ-※-20/※-※-220		20	220	M60X2	70	850	179
HXQ-※-32/※-※-220		32				1165	223
HXQ-※-40/※-※-220	10-42	40				1380	253
HXQ-※-50/※-※-220		50				1640	290
HXQ-※-60/※-※-220		60				1905	327
HXQ-※-80/※-※-220		80				2430	400
HXQ-※-40/※-※-250		40	250	M60X2	70	1205	299
HXQ-※-50/※-※-250		50				1410	334
HXQ-※-60/※-※-250	10-42	60				1615	389
HXQ-※-80/※-※-250		80				2020	435
HXQ-※-100/※-※-250		100				2430	503
HXQ-※-120/※-※-250		120				2840	572

型号/Model	公称压力 Nominal P MPa	公称容积 Nominal V L	基本尺寸Dimensions(mm)				重量/Weight (Kgl)
			ΦD	M	ΦD1	L±3	
HXQ-※-100/※-※-350	10-42	100	350	M72X2	80	1560	836
HXQ-※-120/※-※-350		120				1770	912
HXQ-※-130/※-※-350		130				1870	948
HXQ-※-150/※-※-350		150				2090	1025
HXQ-※-200/※-※-350		200				2600	1113
HXQ-※-215/※-※-350		215				2755	1171
HXQ-※-130/※-※-400	10-42	130	400	M72X2	80	1620	1136
HXQ-※-150/※-※-400		150				1780	1206
HXQ-※-180/※-※-400		180				2020	1310
HXQ-※-200/※-※-400		200				2180	1379
HXQ-※-250/※-※-400		250				2570	1548
HXQ-※-300/※-※-400		300				2965	1823
HXQ-※-350/※-※-400		350				3370	1896

#### ❖ 四、订货说明/Booking Note

1. 活塞式蓄能器为:HXQ-L-50/20-Y-250,表示公称容积为50L,公称压力为20MPa,螺纹连接且油端为M72x2,工作介质为液压油,缸径为Φ250.

2. 本企业对上述产品拥有设计更改权,对修改不另行通知!

1. Piston accumulator:HXQ-L-50/20-Y-250, Nominal volume is 50L, Nominal pressure is 20Mpa thread connection, Medium is Hydraulic liquid, bore is Φ250.

2. Design change is retained by our company and amendment is effected without further notice.

#### ❖ 五、特殊订购/Special order

除以上结构尺寸外,用户如对ΦD(缸径),压力,连接方式(F),工作介质,工作温度,进气端和出油端提出特殊要求,请与本企业商洽.

Contact us if special requirement is needed, custom made are welcome.