

# 蓄能器用NXQ型胶囊/Bladder for NXQ accumulator

## ❖ 一、概述/General Description

本型号的胶囊有耐油、耐酸碱、耐掘挠、强度高、寿命长等特点，符合中国 HG/2331-92标准和ASME标准。

Bladder advantages of enduring oil, acid-and-alkali and Bend resistance, high strength and long useful time and meets the Chine standard of HG/2331-92 and ASME.

## ❖ 二、型号说明/Ordering Code



## ❖ 三、外形尺寸/Dimension



## ❖ 四、技术规格/Technical Parameter

蓄能器规格 Volume(L)		基本尺寸(mm) Dimension					蓄能器规格 Volume(L)		基本尺寸(mm) Dimension					蓄能器规格 Volume(L)		基本尺寸(mm) Dimension				
Φ	L	A	A1	R	DM	Φ	L	A	A1	R	DM	Φ	L	A	A1	R	DM			
89	0.4	74	44	-	M24x1.5	219	16	569	60	95	M30x1.5	299	50	950	70	131	M30x1.5			
89	0.63	144	44	38.5	M24x1.5	219	25	877	60	95	M30x1.5	299	63	1180	70	131	M50x1.5			
114	1	150	44	49	M24x1.5	219	32	1115	60	95	M30x1.5	299	80	1480	70	131	-			
152	1.6	144	49	66	M30x1.5	219	40	1405	60	95	M30x1.5	299	100	1880	70	131	-			
152	2.5	206	49	66	M30x1.5	219	50	1475	60	95		351	80	1090	70	150				
152	4	312	49	66	M30x1.5	299	20	380	70	131	M30x1.5	351	100	1360	70	150				
152	6.3	486	49	66	M30x1.5	299	25	470	70	131	M50x1.5	351	125	1680	70	150				
219	10	365	60	95	M30x1.5	299	40	740	70	131		351	160	2150	70	150				

## ❖ 五、订货说明/Booking Note

1. 订货时须写明型号代号全称，如：容量为40L，直径Φ219，长度为1405mm的(NXQ系列)蓄能器胶囊：40L×1405-219-※
2. 如对本产品此型胶囊有特殊要求时，请同本企业商洽。
3. 本企业保留设计更改权，对修改不另行通知。

1. Full type code is needed when booking For example: Bladder for accumulator(NXQ series)of operating pressure:31.5MPa volume: 40L;diameter: Φ219;Length:1405mm.40L × 1405-219-NBR.
2. Contact us if special requirement is needed
3. Design change is retained by our company and amendment is effected without further notice